IN THE CLAIMS

1. (Currently Amended) A method for detecting the bus width of and then using a

peripheral device connected to an electronic device, wherein at least one bus width

from a determined set of bus widths is available in the peripheral device, wherein for

comprising:

_____detecting the bus width or widths available for use in the peripheral

device[[,]] by detecting one or more indirect indicators formed in the peripheral

device are used, which one or more indirect indicators is itself or are themselves

only indirectly indicative of which one or ones of said set of bus widths are available

for use in the peripheral device.device, said electronic device then

_____using said peripheral device according to the detected bus width or widths.

2. (Previously Presented) The method according to claim 1, wherein reference data

is stored in the electronic device about at least one bus width available in the

peripheral device and corresponding to said indirect indicator value.

3. (Previously Presented) The method according to claim 2, wherein said indirect

indicator used is information stored in the peripheral device and indicating

indirectly, which one or ones of said set of bus widths are available in the peripheral

device.

4. (Previously Presented) The method according to claim 3, wherein said data stored

in the peripheral device is information about the maximum clock frequency

available in the peripheral device.

5. (Previously Presented) The method according to claim 3, wherein at least a fast peripheral device and a slow peripheral device are defined, wherein said information stored in the peripheral device is information about whether the peripheral device is fast or slow.

6. (Previously Presented) The method according to claim 3, wherein said one or more indirect indicators formed in the peripheral device is or are information about a version of the peripheral device.

7. (Currently Amended) The method according to claim 2, comprising performing at least the following:

a request, in whichtransmitting a request is transmitted from the electronic device to the peripheral device to transmit a value of said indirect indicator to the electronic device,

a reply, in which transmitting said indirect indicator value is transmitted from the peripheral device to the electronic device,

an identification, in which comparing said indirect indicator value is compared with at least one reference value stored in the electronic device for determining the bus width or widths available for use in the peripheral device,

a selection for selecting one bus width available in the peripheral device according to said identification, and

a setting for setting the selected bus width for the peripheral device.

8. (Previously Presented) The method according to claim 1, wherein at least one connection line is formed between the electronic device and the peripheral device, and using at least one said connection line as said indicator.

9. (Previously Presented) The method according to claim 8, comprising performing at least the following:

an initialization, in which the value of said at least one connection line is set to correspond indirectly to the bus widths available in the peripheral device,

a detection, in which the electronic device examines the state of said at least one connection line and compares the state of said connection line with at least one reference value stored in the electronic device,

a selection for selecting one bus width available in the peripheral device, and

a setting for setting the selected bus width for the peripheral device.

10. (Previously Presented) A system comprising an electronic device, a peripheral device which can be connected to the electronic device and in which at least one bus width is arranged to be used from a defined set of bus widths, and which system comprises a bus width detector for detecting at least one bus width available in the peripheral device connected to the electronic device, wherein the peripheral device is provided with one or more indirect indicators, which one or more indirect indicators is itself or are themselves only indirectly indicative of which one or ones from said set of bus widths are available in the peripheral device.

11. (Previously Presented) An electronic device comprising a bus width detector for detecting the bus width of a peripheral device connected to the electronic device, in which peripheral device at least one bus width is arranged to be used from a defined set of bus widths, the detector also comprising a control unit for determining the value of one or more indirect indicators formed in the peripheral device, which one or more indirect indicators is itself or themselves only indirectly indicative of which one or ones of said set of bus widths are available in the peripheral device.

12. (Previously Presented) The electronic device according to claim 11, wherein reference data is stored in the electronic device about at least one bus width available in the peripheral device and corresponding to said indirect indicator value.

13. (Previously Presented) The electronic device according to claim 12, wherein said indirect indicator arranged to be used is information stored in the peripheral device and indicating indirectly, which one or ones of said set of bus widths are available in the peripheral device.

14. (Previously Presented) The electronic device according to claim 13, wherein at least one connection line is formed between the electronic device and the peripheral device, and that said indirect indicator arranged to be used is at least one said connection line.

15. (Previously Presented) The electronic device according to claim 14, said detector comprising means for examining a value of said connection line.

16. (Previously Presented) A peripheral device which can be connected to an electronic device comprising a bus width detector for detecting the bus width of the peripheral device connected to the electronic device, and in which peripheral device at least one bus width from a defined set of bus widths is arranged to be used, wherein the peripheral device is provided with one or more indirect indicators which is itself or are themselves only indirectly indicative of which one or ones of said set of bus widths are available in the peripheral device.

17. (Previously Presented) The peripheral device according to claim 16, wherein information about the maximum clock frequency available in the peripheral device is stored in a memory of the peripheral device.

18. (Previously Presented) The peripheral device according to claim 16, wherein at least a fast peripheral device and a slow peripheral device have been defined, wherein information about whether the peripheral device is fast or slow is stored in a memory of the peripheral device.

19. (Previously Presented) The peripheral device according to claim 16, wherein information about version of the peripheral device is stored in a memory of the peripheral device.

20. (Previously Presented) The peripheral device according to claim 16, comprising at least one connection line, and a control unit for setting said connection line in a

value which indirectly corresponds to the bus widths available in the peripheral device.

21. (Previously Presented) A memory card which can be connected to an electronic device comprising a bus width detector for detecting the bus width of the memory card connected to the electronic device, and in which memory card at least one bus width from a defined set of bus widths is arranged to be used, wherein the memory card is provided with one or more indirect indicators which is itself or are themselves only indirectly indicative of which one or ones of said set of bus widths are available in the memory card.

22. (Currently Amended) An electronic device comprising a bus width detector for detecting the bus width of a peripheral device connected to the electronic device, in which peripheral device at least one bus width is arranged to be used from a defined set of bus widths, the bus width detector also comprising means for determining the value of one or more indirect indicators formed in the peripheral device, which one or more indirect indicators is itself or themselves only indirectly indicative of which one or ones of said set of bus widths are available in the peripheral device.

23. (Previously Presented) The electronic device according to claim 22, wherein reference data is stored in the electronic device about at least one bus width available in the peripheral device and corresponding to said indirect indicator value.

24. (Previously Presented) A peripheral device which can be connected to an electronic device comprising a bus width detector for detecting the bus width of the peripheral device connected to the electronic device, and in which peripheral device at least one bus width from a defined set of bus widths is arranged to be used, wherein the peripheral device is provided with one or more indirect indicators which is itself or are themselves only indirectly indicative of which one or ones of said set of bus widths are available in the peripheral device.

25. (Previously Presented) The peripheral device according to claim 16, comprising at least one connection line, and a control unit for setting said connection line in a value which indirectly corresponds to the bus widths available in the peripheral device.